

Cisco Catalyst Blade Switch 3040 for FSC

The Cisco® Catalyst® Blade Switch 3040 for FSC (Figure 1) is an integrated switch for Fujitsu Siemens Computers (FSC) PRIMERGY Blade Server customers that extends Cisco infrastructure services to the server edge and uses existing network investments to help reduce operational expenses.

Figure 1. Cisco Catalyst Blade Switch 3040 for FSC



Designed for the Fujitsu Siemens Computers PRIMERGY Blade Server chassis, the Cisco Catalyst Blade Switch 3040 for FSC helps ensure consistency across the network for advanced services such as security and resiliency. It also allows customers to use the end-to-end Cisco management framework to simplify ongoing operations.

CONFIGURATION

The Cisco Catalyst Blade Switch 3040 provides the following hardware configuration:

- 10 internal 1000BASE ports connected to servers through the PRIMERGY chassis backplane
- 4 external 10/100/1000 Small Form-Factor Pluggable (SFP)-based ports; it supports copper and fiber SX SFP modules from Cisco Systems®
- 2 external 10/100/1000BASE-T ports
- 1 external console port

Available with the Cisco IOS® Software LAN Base image, the Cisco Catalyst Blade Switch 3040 offers a complete set of intelligent services to deliver security, quality of service (QoS), and availability in the server farm access environment.

INTELLIGENCE IN THE SERVER ACCESS NETWORK

As companies increasingly rely on the network as the strategic business infrastructure, and with servers having Gigabit Ethernet capabilities, it is more important than ever to consistently help ensure network security, high availability, and QoS—from the server edge out to the clients at the network edge.

Cisco Catalyst switches, including the Cisco Catalyst Blade Switch 3040, enable companies to realize the full benefits of adding intelligent services into their networks. These capabilities make the server network infrastructure:

- Secure to protect confidential information
- Highly available to meet time-critical needs
- Scalable to accommodate future growth
- Capable of differentiating and controlling traffic flows to handle the increasing number of critical business applications

Enhanced Security

With the wide range of security features that the Cisco Catalyst Blade Switch 3040 offers, businesses can protect important information, keep unauthorized people off of the network, guard privacy, and maintain uninterrupted operation.

To guard against denial-of-service and other attacks, access control lists (ACLs) can be used to restrict access to sensitive portions of the network, blocking unauthorized access to servers and applications by denying packets based on source and destination MAC addresses, IP addresses, or Transmission Control Protocol/User Datagram Protocol (TCP/UDP) ports. ACL lookups are done in hardware, so forwarding performance is not compromised when ACL-based security is implemented.

Port security can be used to limit access on an Ethernet port based on the MAC address of the device to which it is connected. It can also limit the total number of devices plugged into a switch port, reducing the risks of unauthorized servers being plugged into the blade enclosure.

Secure Shell (SSH) Protocol, Kerberos, and Simple Network Management Protocol Version 3 (SNMPv3) encrypt administrative and network management information, protecting the network from tampering or eavesdropping. TACACS+ and RADIUS authentication enable centralized access control of switches and restrict unauthorized users from altering the configurations. Alternatively, a local username and password database can be configured on the switch itself. Fifteen levels of authorization on the switch console and two levels on the Web-based management interface provide the ability to give different levels of configuration capabilities to different administrators.

The MAC Address Notification feature can be used to monitor the network and track servers by sending an alert to a management station so that network administrators know when and where servers are plugged into or removed from a blade enclosure. The Dynamic Host Configuration Protocol (DHCP) Interface Tracker (Option 82) feature tracks where a server is physically connected on a network by providing both the switch and the port ID to a DHCP server.

The Private VLAN Edge feature isolates ports on a switch, helping to ensure that traffic travels directly from the entry point to the aggregation device through a virtual path and cannot be directed to another port. This can help isolate a server from other servers in the same blade enclosure.

High Availability

The Cisco Catalyst Blade Switch 3040 offers several high-availability features to minimize network downtime, maintain mission-critical servers and applications, and reduce total cost of ownership.

Enhancements to the standard Spanning Tree Protocol such as Per-VLAN Spanning Tree Plus (PVST+), UplinkFast, and PortFast maximize network uptime. PVST+ allows for Layer 2 load sharing on redundant links to efficiently use the extra capacity inherent in a redundant design. UplinkFast, PortFast, and BackboneFast help reduce the standard 30-second to-60-second Spanning Tree Protocol convergence time. Loop Guard and Bridge Protocol Data Unit (BPDU) Guard provide Spanning Tree Protocol loop avoidance.

Customers can achieve maximum power and cooling availability for a server farm data network when a Cisco Catalyst Blade Switch 3040 uses the redundant power and cooling capabilities of the blade enclosure.

Advanced QoS

The Cisco Catalyst Blade Switch 3040 offers superior multilayer, granular QoS features to avoid congestion and help ensure that network traffic is properly classified and prioritized. The Cisco Catalyst Blade Switch 3040 can classify, police, mark, queue, and schedule incoming packets and can queue and schedule packets at egress. Packet classification allows the network elements to discriminate between various traffic flows and to enforce policies based on Layer 2 and Layer 3 QoS fields.

To implement QoS, the Cisco Catalyst Blade Switch 3040 first identifies traffic flows or packet groups and classifies or reclassifies these groups using the differentiated services code point (DSCP) field or the 802.1p class-of-service (CoS) field. Classification can be based on criteria as specific as the source/destination IP address, source/destination MAC address, or Layer 4 TCP/UDP port. At the ingress, the Cisco Catalyst Blade Switch 3040 will also police to determine whether a packet is in or out of profile, mark to change the classification label, pass through or drop out of profile packets, queue packets based on classification, and service based on configured weights. Control plane and data plane ACLs are supported on all ports to help ensure proper treatment on a per-packet basis. The Cisco Catalyst Blade Switch 3040 supports four egress queues per port, which allows the network administrator to be discriminating and specific in assigning priorities for the various applications in the server farm. At egress, the switch performs scheduling and congestion control. Scheduling is a process that determines the order in which the queues are processed. The Cisco Catalyst Blade Switch 3040 supports Shaped Round Robin (SRR) and strict priority queuing. The SRR queuing algorithm helps to ensure differential prioritization.

Management

The Catalyst Blade Switch 3040 comes with an embedded GUI device manager that simplifies initial configuration of a switch. Users now have the option to set up the switch through a Web browser. Users familiar with the Cisco command-line interface (CLI) can also use the CLI to do initial configuration and setup. Hence, users do not need any retraining.

Cisco Catalyst Blade Switch 3040 provides for extensive management using SNMP network management platforms such as CiscoWorks for Switched Internetworks. Managed with CiscoWorks, Cisco Catalyst switches can be configured and managed to deliver end-to-end device, VLAN, traffic, and policy management. As part of CiscoWorks, the Web-based Cisco Resource Manager Essentials (RME) offers automated inventory collection, software deployment, easy tracking of network changes, views into device availability, and quick isolation of error conditions.

Product Specifications

Table 1 describes product features and benefits.

Table 1. Product Features and Benefits

Category	Features and Benefits
Ease of Use and Ease of Deployment	<ul style="list-style-type: none">• Device Manager simplifies initial configuration using a Web browser.• DHCP autoconfiguration of multiple switches through a boot server eases switch deployment.• Autosensing detects the speed of the upstream switch and automatically configures each 10/100/1000 uplink port for 10-, 100-, or 1000-Mbps operation, easing switch deployment in mixed 10, 100, and 1000BASE-T environments.• Autonegotiating on 10/100/1000 ports automatically selects half- or full-duplex transmission mode to optimize bandwidth.• Dynamic Trunking Protocol (DTP) enables dynamic trunk configuration across all switch ports.• Port Aggregation Protocol (PAgP) automates the creation of Cisco Fast EtherChannel[®] groups or Gigabit EtherChannel groups to link to the upstream switch/router or server blades.• Link Aggregation Control Protocol (LACP) allows the creation of Ethernet channeling with upstream switches that conform to IEEE 802.3ad and is similar to Cisco EtherChannel technology and PAgP.• Auto-media-dependent interface crossover (MDIX) automatically adjusts transmit and receive pairs if an incorrect cable type (crossover or straight-through) is installed on a copper 10/100/1000BASE-T port.• IEEE 802.3z-compliant 1000BASE-SX and 1000BASE-T physical interface support through a field-replaceable SFP module provides superior flexibility in switch deployment.• DHCP Relay allows a DHCP relay agent to broadcast DHCP requests to the network DHCP server.• The default configuration stored in Flash memory helps ensure that the switch can be quickly connected to the network and can pass traffic with minimal user intervention.

Category	Features and Benefits
Availability and Scalability	
Superior Redundancy for Fault Backup	<ul style="list-style-type: none"> • Cisco UplinkFast and BackboneFast technologies help to ensure quick failover recovery, enhancing overall network stability and reliability. • IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) provides rapid spanning-tree convergence independent of spanning-tree timers. • Per-VLAN Rapid Spanning Tree (PVRST+) allows rapid spanning-tree reconvergence on a per-VLAN spanning-tree basis, without requiring the implementation of spanning-tree instances. • PVST+ allows for Layer 2 load sharing on redundant links to efficiently use the extra capacity inherent in a redundant design. • Unidirectional Link Detection (UDLD) and Aggressive UDLD allow unidirectional links to be detected and disabled to avoid problems such as spanning-tree loops. • Switch port autorecovery (errdisable) automatically attempts to reenables a link that is disabled because of a network error. • Power and cooling resiliency by using redundant power and cooling capabilities from the blade enclosure is provided. • Bandwidth aggregation of up to 6 Gbps through Gigabit EtherChannel technology enhances fault tolerance and offers higher-speed aggregated bandwidth between this integrated switch and upstream switches/routers. • Per-port broadcast, multicast, and unicast storm control prevents faulty servers from degrading overall systems performance. • IEEE 802.1D Spanning Tree Protocol support for redundant backbone connections and loop-free networks simplifies network configuration and improves fault tolerance. • IEEE 802.1s Multiple Spanning Tree Protocol (MSTP) allows a spanning-tree instance per VLAN and enables each VLAN to use a different uplink, allowing better utilization of uplinks. • VLAN1 minimization allows VLAN1 to be disabled on any individual VLAN trunk link. • VLAN Trunking Protocol (VTP) pruning limits bandwidth consumption on VTP trunks by flooding broadcast traffic only on trunk links required to reach the destination devices. • Internet Group Management Protocol (IGMP) snooping provides fast client joins and leaves of multicast streams and limits bandwidth-intensive video traffic to only the requestors. • Multicast VLAN Registration (MVR) continuously sends multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. • FlexLink is a Layer 2 availability feature that can coexist with spanning tree. FlexLink allows convergence time of less than 50 milliseconds on switch uplink ports and remains consistent regardless of the number of VLANs or MAC addresses configured on those ports. • The Trunk Failover feature allows rapid failover to the redundant switch in the blade enclosure if all uplinks from the primary switch fail. When the uplinks fail, the switch shuts down the ports connected to the blade servers and lets network interface card (NIC) teaming software direct traffic to the redundant switch. This feature is also known as Link State Tracking.
QoS	
Advanced QoS	<ul style="list-style-type: none"> • 802.1p CoS and DSCP field classification is provided, using marking and reclassification on a per-packet basis by source and destination IP address, source and destination MAC address, or Layer 4 • TCP/UDP port number. • Cisco control-plane and data-plane QoS ACLs on all ports help to ensure proper marking on a per-packet basis. • 4 egress queues per port enable differentiated management of up to 4 traffic flows. • Shaped Round Robin scheduling helps to ensure differential prioritization of packet flows by intelligently servicing the egress queues. • Weighted Tail Drop (WTD) provides congestion avoidance at the ingress and egress queues before a disruption occurs. • Strict priority queuing guarantees that the highest-priority packets are serviced ahead of all other traffic. • There is no performance penalty for highly granular QoS functions (for example, granular rate limiting). • The Cisco Committed Information Rate (CIR) function guarantees bandwidth in increments as low as 8 Kbps. • Rate limiting is provided based on source and destination IP address, source and destination MAC address, Layer 4 TCP/UDP information, or any combination of these fields, using QoS ACLs (IP ACLs or MAC ACLs), class maps, and policy maps. • Asynchronous data flows upstream and downstream from the end station or on an uplink are easily managed using ingress policing and egress shaping. • Up to 64 aggregate or individual policers per port are allowed.
Security	

Category	Features and Benefits
Networkwide Security Features	<ul style="list-style-type: none"> • IEEE 802.1x allows dynamic, port-based security, providing server authentication. • IEEE 802.1x with VLAN assignment allows a dynamic VLAN assignment for a specific server, regardless of where the server is connected. • IEEE 802.1x and port security are provided to authenticate the port and manage network access for all MAC addresses, including those of the server. • IEEE 802.1x with an ACL assignment allows for specific identity-based security policies, regardless of where the server is connected. • IEEE 802.1x with Guest VLAN allows servers without 802.1x clients to have limited network access on the guest VLAN. • Cisco security VLAN ACLs (VACLs) on all VLANs prevent unauthorized data flows from being bridged within VLANs. • Port-based ACLs (PACLs) allow security policies to be applied on individual switch ports. • SSH Protocol (v2), Kerberos, and SNMPv3 provide network security by encrypting administrator traffic during Telnet and SNMP sessions. SSH, Kerberos, and the cryptographic version of SNMPv3 require a special cryptographic software image because of U.S. export restrictions. • Secure Sockets Layer (SSL) provides a secure means to use Web-based tools such as HTML-based device managers. • Private VLAN Edge provides security and isolation between switch ports, helping to ensure that users cannot snoop on other users' traffic. • Bidirectional data support on the Switched Port Analyzer (SPAN) port allows the Cisco Secure Intrusion Detection System (IDS) to take action when an intruder is detected. • TACACS+ and RADIUS authentication enables centralized control of the switch and restricts unauthorized users from altering the configuration. • MAC address notification allows administrators to be notified of servers added to or removed from the network. • Port security secures the access to an access or trunk port based on the MAC address. • After a specified time, the aging feature removes the MAC address from the switch to allow another server to connect to the same port. • Multilevel security on console access prevents unauthorized users from altering the switch configuration. • The user-selectable address-learning mode simplifies configuration and enhances security. • BPDU Guard shuts down Spanning Tree Protocol PortFast-enabled interfaces when BPDUs are received to avoid accidental topology loops. • Spanning Tree Root Guard (STRG) prevents edge devices not in the network administrator's control from becoming Spanning Tree Protocol root nodes. • IGMP filtering provides multicast authentication by filtering out nonsubscribers and limits the number of concurrent multicast streams available per port. • Dynamic VLAN assignment is supported through implementation of the VLAN Membership Policy Server (VMPS) client function to provide flexibility in assigning ports to VLANs. Dynamic VLAN enables the fast assignment of IP addresses. • 1000 security access control entries are supported.
Manageability	
	<ul style="list-style-type: none"> • Cisco IOS Software CLI support provides a common user interface and command set with all Cisco routers and Cisco Catalyst desktop switches. Cisco Service Assurance Agent (SAA) support facilitates service-level management throughout the LAN. • VLAN trunks can be created from any port, using either standards-based 802.1Q tagging or the Cisco Inter-Switch Link (ISL) VLAN architecture. • Up to 1005 VLANs per switch and up to 128 spanning-tree instances per switch are supported. • 4096 VLAN IDs are supported. • Cisco VTP supports dynamic VLANs and dynamic trunk configuration across all switches. • IGMP snooping provides fast client joins and leaves of multicast streams and limits bandwidth-intensive video traffic to only the requestors. • Remote Switch Port Analyzer (RSPAN) allows administrators to remotely monitor ports in a Layer 2 switch network from any other switch in the same network. • For enhanced traffic management, monitoring, and analysis, the Embedded Remote Monitoring (RMON) software agent supports 4 RMON groups (history, statistics, alarms, and events). • Layer 2 traceroute eases troubleshooting by identifying the physical path that a packet takes from source to destination. • All 4 RMON groups are supported through a SPAN port, which permits traffic monitoring of a single port, a group of ports from a single network analyzer, or an RMON probe. • The Domain Name System (DNS) provides IP address resolution with user-defined device names. • Trivial File Transfer Protocol (TFTP) reduces the cost of administering software upgrades by downloading from a centralized location. • Network Time Protocol (NTP) provides an accurate and consistent timestamp to all intranet switches. • Multifunction LEDs per port for port status and switch-level status LEDs for system indicate status.
Device Manager	<ul style="list-style-type: none"> • Device Manager simplifies initial configuration of a switch through a Web browser. • The Web interface enables less-skilled personnel to quickly and simply set up switches, thereby reducing the cost of deployment.

Category	Features and Benefits
CiscoWorks Support	<ul style="list-style-type: none"> • CiscoWorks network-management software provides management capabilities on a per-port and per-switch basis, providing a common management interface for Cisco routers, switches, and hubs. • SNMP v1, v2c, and v3 and Telnet interface support deliver comprehensive in-band management, and a CLI-based management console provides detailed out-of-band management. • Cisco Discovery Protocol versions 1 and 2 enable a CiscoWorks network-management station for automatic switch discovery.

Table 2 provides hardware information.

Table 2. Hardware

Description	Specification
Performance	<ul style="list-style-type: none"> • 32-Gbps switching fabric • Forwarding rate based on 64-byte packets: up to 24 Mpps • 128 MB DDR SDRAM and 32 MB Flash memory • Configurable up to 8192 MAC addresses • Configurable up to 1000 IGMP groups and bridging entries • Configurable maximum transmission unit (MTU) of up to 9018 bytes (jumbo frames)
Connectors and Cabling	<ul style="list-style-type: none"> • Two 10/100/1000BASE-T ports: RJ-45 connectors; 2-pair Category 5 UTP cabling • Four SFP-based ports: supports copper fiber connectors from Cisco <ul style="list-style-type: none"> ◦ 1000BASE-T SFP-based connectors, 2-pair Category 5 UTP cabling ◦ 1000BASE-SX, LC fiber connectors (single-mode or multimode fiber) • Management console port: RJ-45-to-DB9 cable for PC connections
Power Consumption	<ul style="list-style-type: none"> • 12V @ 3A (36 W)
Indicators	<ul style="list-style-type: none"> • Total of 8 LEDs on the face plate <ul style="list-style-type: none"> ◦ 6 per-port LEDs for uplink port status: displays link, status, and errors ◦ 1 console LED ◦ 1 status LED for FSC enclosure management
Dimensions (H x W x D)	<ul style="list-style-type: none"> • 1.26 x 5.11 x 9.89 in. (3.2 x 12.9 x 25.1 cm)
Weight	<ul style="list-style-type: none"> • 2.0 lb (0.9 kg)
Environmental Ranges	<ul style="list-style-type: none"> • Operating temperature: 0 to 40°C • Storage temperature: 20 to 70°C • Operating relative humidity: 10 to 90% noncondensing • Storage relative humidity: 10 to 95% noncondensing
Predicted Mean Time Between Failure (MTBF)	<ul style="list-style-type: none"> • 400,000 hr

Table 3 provides management and standards support information.

Table 3. Management and Standards Support

Description	Specification
MIB Support	<ul style="list-style-type: none"> • BRIDGE-MIB (RFC1493) • CISCO-CDP-MIB • CISCO-CLUSTER-MIB • CISCO-CONFIG-MAN-MIB • CISCO-ENTITY-FRU-CONTROL-MIB • CISCO-ENVMON-MIB • CISCO-FLASH-MIB • CISCO-FTP-CLIENT-MIB • CISCO-IGMP-FILTER-MIB • CISCO-IMAGE-MIB • CISCO-IP-STAT-MIB • CISCO-MAC-NOTIFICATION-MIB

Description	Specification
	<ul style="list-style-type: none"> • CISCO-MEMORY-POOL-MIB • CISCO-PAGP-MIB • CISCO-PING-MIB • CISCO-PROCESS-MIB • CISCO-RTTMON-MIB • CISCO-STP-EXTENSIONS-MIB • CISCO-SYSLOG-MIB • CISCO-TCP-MIB • CISCO-VLAN-IFTABLE-RELATIONSHIP-MIB • CISCO-VLAN-MEMBERSHIP-MIB • CISCO-VTP-MIB • ENTITY-MIB • ETHERLIKE-MIB • IF-MIB (in and out counters for VLANs are not supported) • IGMP-MIB • OLD-CISCO-CHASSIS-MIB • OLD-CISCO-FLASH-MIB • OLD-CISCO-INTERFACES-MIB • OLD-CISCO-IP-MIB • OLD-CISCO-SYS-MIB • OLD-CISCO-TCP-MIB • OLD-CISCO-TS-MIB • RFC1213-MIB (per the agent capabilities specified in CISCO-RFC1213-CAPABILITY.my) • RFC1253-MIB • RMON-MIB • RMON2-MIB • SNMP-FRAMEWORK-MIB • SNMP-MPD-MIB • SNMP-NOTIFICATION-MIB • SNMP-TARGET-MIB • SNMPv2-MIB • TCP-MIB • UDP-MIB

Table 4 gives safety and compliance information.

Table 4. Safety and Compliance

Description	Specification
<p>Safety Certifications</p>	<ul style="list-style-type: none"> • UL/C-UL: UL/CSA 60950-1, First Edition: Standard for Information Technology Equipment—Safety-Part 1: General Requirements • TUV/GS: EN60950-1, First Edition: Standard for Information Technology Equipment—Safety-Part 1: General Requirements • International: CB report to IEC 60950-1, First Edition (2001) with all deviations

Description	Specification
Electromagnetic Compatibility Certifications	<ul style="list-style-type: none"> • USA: FCC CFR 47 Part 2 and 15, Verified Class A Limit • Canada: IC ICES-003 Class A Limit • International: CISPR 22, Class A Limit • Europe: EMC Directive, 89/336/EEC <ul style="list-style-type: none"> ◦ EN55022, Class A Limit, Radiated & Conducted Emissions ◦ EN55024 ITE Specific Immunity Standard ◦ EN61000-4-2 ESD Immunity (Level 2 Contact Discharge, Level 3 Air Discharge) ◦ EN61000-4-3 Radiated Immunity (Level 2) ◦ EN61000-4-4 Electrical Fast Transient (Level 2) ◦ EN61000-4-5 AC Surge ◦ EN61000-4-6 Conducted RF ◦ EN61000-4-8 Power Frequency Magnetic Fields ◦ EN61000-4-11 Voltage Dips and Interrupts • Japan: VCCI Class A ITE (CISPR 22, Class A Limit) • Australia/New Zealand: AS/NZS CISPR22, Class A Limit • Korea: MIC • Russia: GOST
Telecommunications	<ul style="list-style-type: none"> • CLEI code
Warranty	<ul style="list-style-type: none"> • 90 days

SERVICE AND SUPPORT

Cisco is committed to minimizing total cost of ownership and offers Technical Support Services to help ensure that Cisco products operate efficiently, remain highly available, and benefit from up-to-date system software. Table 5 describes service and support that is available directly from Cisco and through resellers.

Table 5. Service and Support

Technical Support Services	Features	Benefits
Cisco SMARTnet®	<ul style="list-style-type: none"> • Access to Cisco IOS Software updates • Web access to technical support tools and repositories • 24-hour telephone support through the Cisco Technical Assistance Center (TAC) • Advance replacement of hardware 	<ul style="list-style-type: none"> • Minimizes network downtime through reliable day-to-day support and prompt resolution to critical network issues. • Lowers total cost of ownership by using Cisco networking expertise and knowledge. • Protects your network investment through Cisco IOS Software updates that provide patches and new functionality.

Table 6 gives ordering information.

Table 6. Ordering Information

Part Number	Description
WS-CBS3040-FSC	<ul style="list-style-type: none"> • Cisco Catalyst Blade Switch 3040 for FSC
GLC-SX-MM=	<ul style="list-style-type: none"> • GE SFP, LC connector SX transceiver (short wavelength)
GLC-T=	<ul style="list-style-type: none"> • GE SFP, RJ-45 connector 1000BASE-T
CON-SNT-CBS3040	<ul style="list-style-type: none"> • Cisco SMARTnet with 8x5 Next Business Day (NBD) hardware advance replacement
CON-SNTE-CBS3040	<ul style="list-style-type: none"> • Cisco SMARTnet with 8x5 4-hour hardware advance replacement
CON-SNTP-CBS3040	<ul style="list-style-type: none"> • Cisco SMARTnet with 24x7 4-hour hardware advance replacement
CON-S2P-CBS3040	<ul style="list-style-type: none"> • Cisco SMARTnet with 24x7 2-hour hardware advance replacement

For more information about Cisco products, contact:

- United States and Canada: (toll free) 800 553-6387
- Europe: 32 2 778 4242
- Australia: 612 9935 4107
- Other: 408 526-7209
- <http://www.cisco.com>

For more information about FSC's PRIMERGY Blade Server, contact <http://www.fujitsu-siemens.com/>.



Corporate Headquarters
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

European Headquarters
Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: 31 0 20 357 1000
Fax: 31 0 20 357 1100

Americas Headquarters
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-7660
Fax: 408 527-0883

Asia Pacific Headquarters
Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on the **Cisco.com Website at www.cisco.com/go/offices.**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus • Czech Republic
Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel • Italy
Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal
Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden
Switzerland • Taiwan • Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2006 Cisco Systems, Inc. All rights reserved. CCSP, CCVP, the Cisco Square Bridge logo, Follow Me Browsing, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, the Networkers logo, Networking Academy, Network Registrar, Packet, PIX, Post-Routing, Pre-Routing, ProConnect, RateMUX, ScriptShare, ScriptShare, SlideCast, SMARTnet, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0601R)